

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



(51) International Patent Classification <sup>6</sup> : A23D 9/06, A23L 3/3418		A1	(11) International Publication Number: <b>WO 95/27401</b>
(21) International Application Number: PCT/FI95/00189		(43) International Publication Date: 19 October 1995 (19.10.95)	
(22) International Filing Date: 6 April 1995 (06.04.95)		(81) Designated States: BR, CZ, FI, HU, MX, NO, PL, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(30) Priority Data: 941617 8 April 1994 (08.04.94) FI		Published With international search report. In English translation (filed in Finnish).	
(71) Applicant (for all designated States except US): AGA AK-TIEBOLAG [SE/SE]; S-181 81 Lidingö (SE).			
(72) Inventor; and (75) Inventor/Applicant (for US only): WASASTJERNA, Jan [FI/FI]; Dalvägen 2 A 2, FIN-02700 Grankulla (FI).			
(74) Agent: LEITZINGER OY; Ruoholahdenkatu 8, FIN-00180 Helsinki (FI).			
(54) Title: METHOD FOR EXTENDING THE LIFE TIME OF FAT USED IN DEEP FRYING			
(57) Abstract			
<p>The invention relates to a method for extending the useful life of a deep-frying fat. In the method, into the fat during the deep-frying and possibly the storage an inert gas stream, preferably nitrogen, is fed in finely divided form.</p>			
<p><b>BEST AVAILABLE COPY</b></p>			

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## METHOD FOR EXTENDING THE LIFE TIME OF FAT USED IN DEEP FRYING.

---

The present invention relates to a method for extending the useful life of deep-frying fat.

The relatively fast deterioration of the quality of fat is restraining the useful life of edible oils, e.g. rapeseed oil in deep-drying. The deterioration depends partly on the crumbs which are loosening from the fried products and stay at the bottom of the deep-frying vessel, partly on the changes that occur in the fat through contact with oxygen of the atmosphere, such as increase of the free fat acids and lowering of the smoke point.

The most important deep-fried products are different bakery products, such as donuts and different pasties, meat products such as meat bolls and hamburger steaks, fish products, and deep-fried potatoe products. The products are steaked in the hot edible oil for a necessary time, wherein they are led on a conveyor belt through the frying fat as sinked therein. The in the fat sinked products are absorbing frying fat, fresh oil has hence been added to the frying vessel during the treatment. The steaking ovens are generally provided with an equipment which automatically adds fresh frying fat so that the amount of oil is sufficient.

By deep-frying, the temperature has to be adapted to the product which is to be produced, by frying of donuts the temperature shall be about 180 °C. If the temperature of fat is lower, the donuts absorb too much fat and are therefore not completely fried. Additionally, dough bits and fragments are spoiling the fat blend. A higher temperature leads to burning of donuts, and the burned material ends upp in the fat blend. The above mentioned drawbacks impair the fat quality, reduce its usability and useful life.

A low quality fat gives a qualitatively poor final result. Furthermore, the cleaning and maintaining of the apparatus and the used vessels is more difficult. After ending the frying the fat is pumped to a vessel, e.g. overnight in order to make the cleaning of the frying vessel possible. Low quality fat leaves fat depositions and rests on the walls and bottom of the vessel. These rests make the cleaning more difficult and delay it considerably. Additionally, the contaminated fat is getting spoiled considerably faster.

The object of the present invention is to provide a method, wherein the useful life of the frying fat can be extended considerably while avoiding the above mentioned drawbacks. The invention is characterized in that to the fat used in deep-frying an inert gas, preferably nitrogen, is led. In order to get as even distribution of gas as possible and as effective gas measuring of the fat as possible, the gas is led to the fat in a finely dispersed form.

In a preferred embodiment of the invention a gas is led continuously to the hot fat mixture during frying.

After frying the used fat is led to a storing vessel for storage e.g. overnight. In order to prevent a considerable deterioration of fat quality during the storage, a minor amount of a gas, preferably nitrogen is led over the fat in the vessel or into the fat. The deep-frying device and the other equipment is cleaned during this break in the method.

Preferably the gas is led into the fat stream, which is fed into the deep-frying vessel during the frying, on the pressure side of the fat pump. Depending on the product which is treated the feeding can be carried out continuously or not continuously in suitable portions.

In the following, a method is described wherein the present invention is exploited by supplying the deep-frying fat with

nitrogen gas. By way of comparison the method has also been carried out without supplying nitrogen.

The method is carried out on a meat pasty line, wherein the volume of the deep-frying tank is about 2 m<sup>3</sup> (the volume of a typical industrial deep-frying tank is about 1,5 - 2,5 m<sup>3</sup>). Several tests were carried out one after the other in order to be able to compare the result which has been obtained from the different flows. The purpose of the test was to map out how much the useful life of the frying fat can be extended by means of gas inerting. Thus as comparison a deep-frying fat was used, which wasn't supplied with nitrogen at all during the test, i.e., it's a question of a normally used deep-frying method.

During the method, the quality of the fat was controlled among other things by measuring the amount of the free fat acids (FFA) formed. There exist no criteria for high or low quality fats, but a general recommendation is that if FFA is 2 and the smoke point of the fat is 180°C, the fat shouldn't be used for frying purposes any more.

Frying- or deep-frying fat is pumped in the usual manner to the deep-frying vessel from a storage vessel. The inside of the supplying pipe has been supplied on the pressure side of the pump with one or more nozzles, which have been connected to a nitrogen source. The nozzle can be constituted of a sintered body or a perforated tubular unit, wherein the diameter of the fine openings is about 5 µm. In the reference tests the fat blend was not supplied with nitrogen. During the deep-frying fresh fat was continuously supplied to the frying vessel so that the fat level in the vessel remained rather unchanged. A fat addition is necessary, because the products absorb a certain amount of fat during the frying.

The following results were obtained in the tests which were carried out.

4

Ref.	N <sub>2</sub> -flow m <sup>3</sup> /h	Night flow m <sup>3</sup> /h	Test period	FFA
Ref.	0	0	8 ad	1,87
1.	10 m <sup>3</sup> /h	2 m <sup>3</sup> /h	29 ad (1 ad=1,5 as) 1085,25 h	1,5
2.	5 m <sup>3</sup> /h	2 m <sup>3</sup> /h	18 ad (1 ad=1 as) 583,9 h	1,57
3.	5 m <sup>3</sup> /h	2 m <sup>3</sup> /h	14 ad (1 ad=2 as) 416,4 h	1,8
4.	5 m <sup>3</sup> /h	2 m <sup>3</sup> 1 hour after pumping over	21 ad (1 ad=2 as) 848 h	1,71

-----

ad = working-day

as = work shift

From the results in the table it is evident that nitrogen supply clearly extends the useful life of the fat by deep-frying, i.e. the quality of the fat falls off markedly slower than by the reference test. In the method where no nitrogen was supplied, the quality of the fat thus fell off in 8 days (1 working-day = 1,5 work shift), whereafter the fat had to be changed, because the FFA value approaches the limit value of 2.

The test 1 demonstrates, that by a nitrogen amount of 10 m<sup>3</sup>/h, the FFA limit value hasn't been reached yet after 29 days. Accordingly the fat was still completely usable after such a long utilization.

In test 2, the nitrogen flow has been reduced to 5 m<sup>3</sup>/h, and the test was carried out for 18 days, and during one work shift daily. At the end of the test the quality of the fat was still fully acceptable.

---

The test 3 was carried out with the same nitrogen flow as test 2, but one working-day consisted of two work shifts. The fat consumption is hence greater, but approximately of the same order of magnitude as test 2.

In test 4 the nitrogen flow was again the same as in the two previous tests, even here two shifts were run per day. By the storage, nitrogen was supplied to the reservoir vessel only during one hour after the pumping over of the fat. The test result demonstrates that the quality of the fat is acceptable also after such a long use.

The results obtained show that with the method according to the present invention, a very satisfactory result is reached regarding the quality of the deep-frying fat during a long-term use. Hence the fat can be used during a considerably longer time than by customary deep-frying methods. Not only a reduction in the necessary fat amount is reached but also the cleaning of the frying device and tools is easier.

In the following method, inerting tests are carried out on a fish ball line. The volume of the frying vessel contains 35 litres of a deep-frying fat. The deep-frying fat is normally exchanged once a week. During the deep-frying process, the fried products are absorbing oil. In order to keep an even oil level in the deep-frying vessel, the deep-frying vessel is supplied continuously with 33 litres of fresh oil per day. The deep-frying is carried out for 7,5 hours/day, 5 days a week.


Two deep-frying vessels with identical process conditions are used in the method. The oil in the other of the deep-frying

vessels is inerted with nitrogen (B1), while the other the deep-frying vessel is used as a reference, i.e. the deep-frying is carried out in a normal deep-frying method (B3).

After the day shift oil (B1) is pumped over from the deep-frying vessel to a special vessel. The vessel holds 35-40 litres of oil, and it is provided with a pipe and a nozzle which have been connected to a nitrogen source. The nozzle consists of a perforated tubular unit, in which the diameter of the fine openings are about 5  $\mu\text{m}$ . In the vessel the oil is inerted during 2 hours with 5 litres of nitrogen per minute, thereafter with 2 litres of nitrogen per minute during 10 hours (night storage).

The quality of the fat is controlled by measuring the free fatty acids (FFA) and the peroxide number of the fat, before and after the daily production.

From the result and the following graph it is evident that the nitrogen supply extends the useful life of the oil. In oil supplied with nitrogen as above, the useful life is at least twice as long as in the reference test.





## Claims

1. A method for extending the useable time of deep-frying fat, characterized in that the fat used in the deep-frying is supplied with an inert gas, preferably nitrogen, in a finely divided form.

---

2. The method of claim 1, characterized in that the gas is fed continuously into the hot fat.

3. The method of claim 1, characterized in that the gas is fed not continuously into the hot fat.

4. The method of claim 1, characterized in that between the frying sets the fat is fed to a collecting vessel, wherein gas is fed to the vessel and/or into the fat in the vessel.

5. The method of any of the previous claims, characterized in that the gas is supplied to the stream of frying fat, which is fed into the frying vessel, to the pressure side of the feeding pump.

6. The method of claim 5, characterized in that the gas is fed into the fat stream through one or more nozzles.

7. The method of claim 5 and 6, characterized in that the nozzle(s) is/are arranged into the oil feeding pipe from the feeding pump.

8. The method of claim 6 or 7, characterized in that the nozzle is a sintered body or a tubular unit with perforated walls.

9. The method of claim 8, characterized in that the perforation consists of an aperture with a diameter of the order of magnitude of 5  $\mu\text{m}$ .

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 95/00189

## A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A23D 9/06, A23L 3/3418

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A23D, C11B, A23L

~~Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched~~

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	J. Sci. Fd Agric., Volume 26, 1975, Micha Peled et al, "Effect of Water and BHT on Stability of Cottonseed Oil During Frying", page 1663 - page 1665, abstract	1
Y	page 1663 - page 1665, abstract	1-9
	--	
Y	EP 0580896 A2 (PRAXAIR TECHNOLOGY, INC), 2 February 1994 (02.02.94), page 3, line 40 - page 5, line 1	1-9
	--	
A	GB 2231252 A (FUJI OIL CO. LTD), 14 November 1990 (14.11.90)	1-9
	--	

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

11 July 1995

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Date of mailing of the international search report

13 -07- 1995

Authorized officer

Inger Löfgren  
Telephone No. +46 8 782 25 00

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 95/00189

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	Journal of food science, Volume 51, No 3, 1986, K. Warner et al, "Storage Stability of Soybean Oil-Based Salad Dressings: Effects of Antioxidants and Hydrogenation"	1-9
A	EP 0339491 A1 (AB PROFOR), 2 November 1989 (02.11.89)	1-9
A	WO 9317567 A1 (CALGON CARBON CORPORATION), 16 Sept 1993 (16.09.93)	1-9

# INTERNATIONAL SEARCH REPORT

29/05/95

International application No.

PCT/FI 95/00189

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP-A2-	0580896	02/02/94	NONE		
GB-A-	2231252	14/11/90	JP-A-	2272098	06/11/90
			US-A-	5298271	29/03/94
EP-A1-	0339491	02/11/89	DE-U-	6890027	24/10/91
			SE-B,C-	461005	18/12/89
			SE-A-	8801592	29/10/89
WO-A1-	9317567	16/09/93	CA-A-	2102312	05/09/93
			EP-A,A-	0592622	20/04/94
			JP-T-	6510563	24/11/94
			US-A-	5348755	20/09/94

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE LEFT BLANK**